

7807R-EU

10 mm (3/8") drill



This powerful and high quality drill is ideal for all general purpose drilling, honing, reaming and hole-sawing.

- Powerful motor delivers 0,25 kW (0,33 HP).
- 1 800 rpm free speed.
- Planetary gear reduction balances the load on bearings and gears for increased tool life.
- · Professional steel chuck provides secure bit gripping.
- With its reversible motor, it can also be used for driving and removing screws.
- Variable-speed lever allows precise delivery of power and speed.

Specifications at 6,2 bar (90 psi)

Part Number	7807R-EU
Ordering number	01352160
Chuck capacity	3/8 in / 10 mm
Chuck type	with key
Spindle size	3/8"-24

PERFORMANCE

Rated power	0,33 HP / 0,25 kW
Free speed	1 800 rpm

AIR SYSTEM

Air Inlet (NPTF)	1/4 in
Minimum hose size	10 mm
Average air consumption	4,0 CFM / 113 L/min
Air consumption at load	17.0 CFM / 485 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)	89,2 / 100,2 dB(A)
Vibration level / measurement uncertainty (ISO28927)	25/-m/s²

WEIGHT & DIMENSIONS

Tool weight	2,35 lb / 1,07 kg
Tool dimensions (L x W x H)	206 x 38 x 84 mm
Head dimensions (W x H)	37 x 84 mm
Shipping weight	2,75 lb / 1,25 kg
Shipping dimensions (L x W x H)	110 x 203 x 51 mm
UPC / EAN code	6 63023 00506 5
Origin	Made in Taiwan



www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.





7807R-EU

ACCESSORIES



728-99-KC5 04276564 Keyless chuck, 10 mm



7811-99 89930754 Standard chuck, 10 mm

77NMC2

Lubricants



7811-253 89930762 Key for standard chuck, 10 mm



IB6NMC2 88103015 IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-



Quick Release CouplingsFor the complete range, see our accessory catalogue.



10Z4 03875671 Oil, Class 1, no. 10, 0,12 L



88104070 7N7/7S7 Series nipple, 1/4" male thread, 7,2 mm bore (EURO 7,2 - 7,4)



Filters, regulators, lubricatorsFor the complete range, see our accessory catalogue.



For the complete range, see our accessory catalogue.

www.ingersollrandproducts.com