

116H-EU Hammer



This economical hammer is ideal for fast cutting action.

- Up to 3 500 strokes per minute.
- Alloyed steel barrel and heat-treated piston ensures longer life.
- Variable-speed lever allows precise delivery of power and speed.
- Wide range of power regulator settings helps adjusting the power to the application.

Specifications at 6.2 bar (90 psi)

 Part Number
 116H-EU

 Ordering number
 01343904

 Shank type
 Shank size
 0.401 in / 10.1 mm

 - round shank
 116-EU

 - round shank with 6 chisels
 LA426-EU

 - hexagonal shank with 6 chisels
 LA427-EU

PERFORMANCE

 Piston bore
 11/16 in / 17.5 mm

 Piston stroke
 2-5/8 in / 67 mm

 Strokes per minute
 3 500

AIR SYSTEM

Air Inlet (NPTF)

1/4 in
Minimum hose size

3/8 in / 10 mm
Average air consumption

Air consumption at load

3.0 CFM / 85 L/min
15.0 CFM / 425 L/min

NOISE & VIBRATION

Sound pressure / power (ISO15744)

Vibration level / measurement uncertainty (ISO28927)

101.4 / 112.4 dB(A)

101.8 / 2.2 m/s²

WEIGHT & DIMENSIONS

 Tool weight
 3.40 lb / 1.54 kg

 Tool length
 7.8 in / 198 mm

 Shipping weight
 235 x 65 x 175 kg

 Shipping dimensions (L x W x H)
 4.05 in / 1.84 mm

 UPC / EAN code
 6 63023 00970 4

 Origin
 Made in Taiwan



www.ingersollrandproducts.com

Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.





116H-EU ACCESSORIES



116H-K5

92536093

Chisels, hexagonal shank, 10.2 mm (5 pieces)



116-66H

92684901

Chisel, hexagonal shank, 10.2 mm



116-70H

92684943

Chisel, hexagonal shank, 10.2 mm



116-87H

92684935

Chisel, hexagonal shank, 10.2 mm



116-88H

92684919

Chisel, hexagonal shank, 10.2 mm



116-89H

92684927

Chisel, hexagonal shank, 10.2 mm



9510

80167752

Quick change retainer



115-183

03788510

Spring retainer



33104-45

92938760

Hose whip, 1/4" NPT, 6 mm inside diameter, 45 cm (1.5 ft)



IB6NMC2

88103015

IBN/IBS Series nipple, 1/4" male thread, 6 mm bore (ISO6150B / MIL-C4109)



77NMC2

88104070

7N7/7S7 Series nipple, 1/4" male thread, 7.2 mm bore (EURO 7.2 - 7.4)



Quick Release Couplings

For the complete range, see our accessory catalogue.



Filters, regulators, lubricators

For the complete range, see our accessory catalogue.



10**Z**4

03875671

Oil, Class 1, no. 10, 0.12 L



Lubricants

For the complete range, see our accessory catalogue.



Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of product shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.

