



8000MAX Series

Random Orbital Sanders



MAX Performance. MAX Finish.

In keeping with the tradition of Ingersoll Rand MAX tools, 8000MAX Series Random Orbital Sanders deliver MAX Power and MAX Productivity for all of your body, prep, and finishing work — and now offer a new level of MAX Comfort, with less vibration and a lightweight ergonomic design.

MAX Comfort

Low vibration and lightweight ergonomic design
reduce operator fatigue

MAX Power

Powerful 0.27 hp motor and variable-speed regulator
deliver the performance required for ALL of your finishing jobs

MAX Productivity

Reduced vibration and improved stability increase abrasive pad life and help create a smoother finish

Model	Rated Power (hp/W)	Free Speed (rpm)	Orbit Diameter (mm)	Backing Pad Diameter (mm)	Backing Pad Type	Vacuum-Ready	Vibration* m/s ² , K	Sound Pressure** (dB(A))	Weight lbs. (kg)	Length (mm)	Air Consumption at Load cfm (l/min)
8101MAX	0.27/200	0-11500	3/32" (2.5)	6" (150)	PSA	No	8.6/2.8	76	1.65 (.75)	6.3" (160)	12.7 (360)
8102MAX	0.27/200	0-10500	3/16" (5)	6" (150)	PSA	No	7.0/2.3	76	1.65 (.75)	6.3" (160)	12.7 (360)
8103MAX	0.27/200	0-9500	3/8" (10)	6" (150)	PSA	No	7.9/2.6	76	1.75 (.80)	6.3" (160)	12.7 (360)
8201MAX	0.27/200	0-11500	3/32" (2)	6" (150)	Hook and Loop	Yes	7.2/2.4	76	1.65 (.75)	7.9" (200)	12.7 (360)
8202MAX	0.27/200	0-10500	3/16" (5)	6" (150)	Hook and Loop	Yes	6.9/2.3	76	1.65 (.75)	7.9" (200)	12.7 (360)
8203MAX	0.27/200	0-9500	3/8" (10)	6" (150)	Hook and Loop	Yes	6.8/2.2	76	1.75 (.80)	7.9" (200)	12.7 (360)

Performance figures are at 90 psi air pressure

Air inlet for all modes is 1/4" NPT

Minimum hose size for all models is 5/16" (8mm)

Backing pad screw thread diameter – M8

* (ISO28927)

** (ISO15744)



8100MAX & 8200MAX

8200MAX

Ergonomic grip is uniquely designed with an anti-slip rubber compound, providing the ultimate in comfort and style

Patented throttle lever design provides stable, ergonomic hand support

Exhaust silencer includes a multi-stage noise suppression filter for the quietest operation in its class with no sacrifice in performance



Multi-hole slim backing pad lowers the center of mass, improving tool stability

Double bearing design improves protection of the motor from dust and contaminants, thus increasing durability and performance

8100MAX



Pad wrench storage keeps wrench conveniently available for fast backing pad changes.



ingersollrandproducts.com/maxsanders



Ingersoll Rand (NYSE:IR) advances the quality of life by creating and sustaining safe, comfortable and efficient environments. Our people and our family of brands—including Club Car®, Ingersoll Rand®, Schlage®, Thermo King® and Trane®—work together to enhance the quality and comfort of air in homes and buildings; transport and protect food and perishables; secure homes and commercial properties; and increase industrial productivity and efficiency. Ingersoll Rand products range from complete compressed air systems, tools and pumps to material handling systems. The diverse and innovative products, services and solutions enhance our customers' energy efficiency, productivity and operations. We are a \$14 billion global business committed to a world of sustainable progress and enduring results. For more information, visit ingersollrandproducts.com.



(800) 866-5457 • ingersollrandproducts.com

Distributed by:

Ingersoll Rand, IR and the IR logo are trademarks of Ingersoll Rand, its subsidiaries and/or affiliates. All other trademarks are the property of their respective owners. Nothing contained on these pages is intended to extend any warranty or representation, expressed or implied, regarding the product described herein. Any such warranties or other terms and conditions of sale of products shall be in accordance with Ingersoll Rand's standard terms and conditions of sale for such products, which are available upon request. Product improvement is a continuing goal at Ingersoll Rand. Designs and specifications are subject to change without notice or obligation.