SUPER HAND



Fast, efficient filing, sanding and deburring tools

Features

- Eliminates time consuming manual hand-filing operations
- Ideal for industrial production filing applications on steel, aluminum, brass, wood and other materials
- •Unique and compact design delivers reduced vibration performance while reducing operator fatigue.
- Interchangeable files
- Rear exhaust system



Model ASH-900



Weight reduced by half for comfortable operation over long period of time

Rat Tail File SF-10

Triangular Taper File SF-11

Half Round File SF-12

Flat Bastard File SF-13

| Specifications |
|----------------|
|----------------|

| Model | SH-100A | ASH-900 | |
|----------------------------------|---|---|--|
| Air Pressure MPa {kgf/cm²} | 0.6 {6} | 0.6 {6} | |
| Air Consumption (No load) m³/min | 0.24 | 0.2 | |
| Stroke Speed min ⁻¹ | 3,700 | 6,300 | |
| Stroke Length mm | 9 | 9 | |
| File Shank Size mm | 6.3 | 5.0 | |
| Mass (Weight) kg | 1.1 | 0.5 | |
| Accessories Included | Flat Bastard File SF-13 Rat Tail File SF-10 Triangular Taper File SF-11 Half Rounded File SF-12 3 mm Hex. Socket Screw Key Bushing R 1/4 × NPT 1/4 | Flat Bastard File SF-13 Rat Tail File SF-10 Triangular Taper File SF-11 Half Rounded File SF-12 2.5 mm Hex. Socket Screw Key Bushing R 1/4 × NPT 1/4 | |

Optional Accessories

For Super Hand SH-100A & ASH-900

| i oi oupoi | | |
|------------|-------------------------------|------------|
| PN | Description | Sales Unit |
| TA9A222 | Rat Tail File SF-10 | 5 pcs./set |
| TA9A223 | Triangular Taper File SF-11 | 5 pcs./set |
| TA9A224 | Half Round File SF-12 | 5 pcs./set |
| TA9A225 | Flat Bastard File SF-13 | 5 pcs./set |
| TA91752 | Rubber Pad Ass'y for SH-100A | 1 set |
| TA94625 | Supporter Ass'y for SH-100A | 1 set |
| TB04319 | Sanding Pad Ass'y for ASH-900 | 1 set |
| | | |

it PN TA91752 Rubber Pad Ass'y for SH-100A





PN TA94625 Supporter Ass'y for SH-100A (use with TA91752)



FINISHING FILE SUPER HAND LIGHT FORTABLE FINE MICRO AIR HAND FILING FINISHING FILE

SUPER HAND LIGHT Best suited for deburring of die-cast aluminum products and machined parts




Model **SHL-40**



Specifications

| Model | SHL-40 |
|---|--|
| Air Pressure MPa {kgf/cm ² } | 0.6 {6} |
| Air Consumption (No load) m³/min | 0.07 |
| Stroke Speed min ⁻¹ | 9,000 |
| Stroke Length mm | 4 |
| File Shank Size mm | 3 |
| Mass (Weight) kg | 0.4 |
| Accessories Included | Flat File LF-13 2 mm Hex. Socket Screw Key Bushing R 1/4 × NPT 1/4 |

Optional Accessories Sales Unit (3 pcs/set)



MICRO AIR HAN

Fine reciprocating motion best for precision parts filing

MAH-05/MAH-16



Specifications

| Model | | MAH-05 | MAH-16 | | | |
|--|---|---------|--------|--|--|--|
| Air Pressure M | IPa {kgf/cm²} | 0.6 {6} | | | | |
| Air Consumption (No loa | l d) m³/min | 0.07 | | | | |
| Stroke Speed | min ⁻¹ | 22,000 | 11,000 | | | |
| Stroke | mm | 0.5 | 2.2 | | | |
| Shank diameter of file mm | | 3 | | | | |
| Mass (Weight) | kg | 0.4 | | | | |
| Accessories Included | Flat end fil Round end | | | | | |
| Vice Holder (PN TB07506) This holder can be used for polishing and lap applications by mounting ceramic stones, etc (Max size: Thickness 3.2 mm × Width 20 mm | | | | | | |

Mounting examples

Select either one of the 2 models depending on your applications. 0.5 mm 2.2 mm stroke ctrok **MAH-05 MAH-16** 0.5 2.2

Optional Accessories Sales Unit (5 pcs/set)

